



DSM 800RC – Maximum grinding ease!

Let the Schwamborn DSM 800RC do the grinding. Suitable for very large working surfaces, agile and versatile in use. Display information on current machine performance ensure a uniformly high surface quality and maximum productivity.



Support wheel for transportation



Grinding close to the edge with the remote control



Remote control

Applications

Grinding concrete, screed, industrial floors, asphalt, sticking of concrete, screed and asphalt, large-scale renovation, remove adhesives, coatings, fillers, regulate uneven floors, grinding and polishing concrete, screed, asphalt, natural stone, terrace

Technical data

Ref. No.		716500
Voltage	V	400
Frequency	Hz	50 - 60
Power output	kW	15
Working width	mm	800
No. of tools	mm	3 x 270
Grinding pressure, max.	kg	215/270/160
Operating weight	kg	615
Edge distance	mm	10
Tool speed	r.p.m.	400 – 1200
Tank	l	26
Ø-Dust control	mm	76
Dimensions LxWxH	cm	175 x 84 x 155
Tool mount		ETX1, ETX2, Velcro

Special characteristics

ETX – Tool exchange	ETX-2 tool holder
DIF – Diamond floating device	High-performance load gearbox
MOP – Motor overload protection	Automatic tool adaptation (DIF)
Counter rotating tools	Anti-shock transmission mounting (ASD)
High grinding performance	Crane hook
Remote control	180° turning manoeuvres with overlapping
Adjustable grinding pressure	Automatic movement
Automatic battery charging	Shuttle movement, uniform overlapping
Battery power for loading and unloading	Trimming, uniform grinding straight ahead
Display with power indicator	Display info with tool velocity and speed

DSM 800RC Accessories and tools, grinding from page 48, bush hammering from page 58