

DSM 650RC

DSM 650RC – Maximum grinding ease!

Let the Schwamborn DSM 650RC do the grinding. Suitable for large working surfaces, agile and versatile in use. Display information on current machine performance ensure a uniformly high surface quality and maximum productivity.



Support wheel for transportation



Remote control

Applications

Grinding concrete, screed, industrial floors, asphalt, sticking of concrete, screed and asphalt, large-scale renovation, remove adhesives, coatings, fillers, regulate uneven floors, grinding and polishing concrete, screed, asphalt, natural stone, terrace

Technical data

Ref. No.		729000
Voltage	V	400
Frequency	Hz	50 - 60
Power output	kW	11
Working width	mm	650
No. of tools	mm	3 x 230
Grinding pressure, max.	kg	165/230/120
Operating weight	kg	450
Edge distance	mm	10
Tool speed	r.p.m.	400 – 1200
Tank	l	15
Ø-Dust control	mm	76
Tool mount		ETX1, ETX2, Velcro

Special characteristics

ETX – Tool exchange	Display with power indicator
DIF – Diamond floating device	ETX-2 tool holder
MOP – Motor overload protection	High-performance load gearbox
Counter rotating tools	Anti-shock transmission mounting (ASD)
Speed control	Crane hook
Dead man switch	180° turning manoeuvres with overlapping
Adjustable grinding pressure	Automatic movement
Narrow design for passing through doorways	Shuttle movement, uniform overlapping
Automatic battery charging during operation	Trimming, uniform grinding straight ahead
Battery power for loading and unloading	Display info with tool velocity and speed

DSM 650RC Accessories and tools, grinding from page 48, bush hammering from page 58